

Party:	Width: 44.1 m	Processed by: Beer/Go
Boat/Motor: Trimaran	Area: 81.0 m ²	Mean Velocity: 0.027 m/s
Gage Height: 0.000 m	G.H.Change: 0.000 m	Discharge: 2.16 m ³ /s

Area Method: Avg. Course	ADCP Depth: 0.078 m	Index Vel.: 0.00 m/s	Rating No.: 1
Nav. Method: Bottom Track	Shore Ens.:10	Adj.Mean Vel: 0.00 m/s	Qm Rating: U
MagVar Method: None (0.0°)	Bottom Est: Power (0.1667)	Rated Area: 0.000 m ²	Diff.: 0.000%
Depth: Composite (BT)	Top Est: Power (0.1667)	Control1: Unspecified	
Discharge Method: None		Control2: Unspecified	
% Correction: 0.00		Control3: Unspecified	

Screening Thresholds:		ADCP:	
BT 3-Beam Solution: YES	Max. Vel.: 2.26 m/s	Type/Freq.: Rio Grande / 1200 kHz	
WT 3-Beam Solution: YES	Max. Depth: 2.18 m	Serial #: 3196	Firmware: 10.17
BT Error Vel.: 0.10 m/s	Mean Depth: 1.84 m	Bin Size: 15 cm*	Blank: 25 cm
WT Error Vel.: 1.07 m/s	% Meas.: 47.01	BT Mode: 5	BT Pings: 1
BT Up Vel.: 0.30 m/s	Water Temp.: None	WT Mode: 1	WT Pings: 1
WT Up Vel.: 1.00 m/s	ADCP Temp.: 17.2 °C	WV : 175*	
Use Weighted Mean Depth: YES			

Performed Diag. Test: NO

Performed Moving Bed Test: NO

Performed Compass Calibration: NO

Evaluation: NO

Meas. Location: Ommen

Project Name: 190924hesslm_trim_0.mmt

Software: 2.20

Tr.#		Edge Distance		#Ens.	Discharge						Width	Area	Time		Mean Vel.		% Bad	
		L	R		Top	Middle	Bottom	Left	Right	Total			Start	End	Boat	Water	Ens.	Bins
000	L	0.50	0.00	182	0.615	0.987	0.422	0.049	0.000	2.07	36.2	73.0	13:22	13:22	0.79	0.03	2	10
003	R	4.00	5.00	280	0.357	0.853	0.103	-0.262	-0.428	0.622	46.8	84.6	13:31	13:32	0.52	0.01	1	31
004	L	5.00	5.00	273	0.111	0.316	0.018	0.106	-0.171	0.380	45.2	81.4	13:33	13:34	0.52	0.01	5	43
005	R	4.00	5.00	171	1.01	1.40	0.571	0.403	-0.214	3.17	44.5	80.9	13:35	13:36	0.77	0.04	2	41
006	L	4.00	4.00	234	0.762	1.02	0.273	0.302	-0.151	2.20	44.3	81.5	13:37	13:38	0.58	0.03	2	43
007	R	4.00	4.00	196	0.693	0.609	0.563	0.414	-0.005	2.27	45.4	83.5	13:38	13:39	0.70	0.03	1	40
008	L	4.00	4.00	181	1.34	1.87	0.832	0.294	0.297	4.63	42.8	78.5	13:40	13:40	0.72	0.06	2	40
009	R	4.00	5.00	206	0.988	1.02	0.523	0.245	-0.226	2.56	44.1	80.1	13:41	13:42	0.63	0.03	0	39
010	L	4.00	4.00	196	0.666	0.999	0.488	-0.230	0.122	2.05	44.0	81.2	13:43	13:44	0.69	0.03	2	42
011	R	4.00	4.00	287	0.200	0.420	0.059	-0.251	-0.382	0.045	45.3	82.7	13:45	13:46	0.49	0.00	0	42
012	L	4.00	4.00	189	0.370	1.15	0.558	0.262	0.510	2.85	44.0	81.5	13:47	13:48	0.71	0.04	0	46
013	R	4.00	4.00	186	1.20	1.65	0.528	0.078	0.045	3.50	45.3	82.5	13:49	13:50	0.75	0.04	2	43
014	L	4.00	4.00	216	0.679	0.930	0.370	-0.074	-0.123	1.78	44.9	82.0	13:51	13:52	0.67	0.02	2	43
Mean		3.81	4.00	215	0.691	1.02	0.408	0.103	-0.056	2.16	44.1	81.0	Total	00:30	0.66	0.03	2	39
SDev		1.03	1.29	40	0.373	0.442	0.237	0.244	0.261	1.28	2.5	2.8			0.10	0.02		
SD/M		27.1%	32.3%	18.8%	54.0%	43.4%	58.0%	237.1%	467.5%	59.3%	5.8%	3.5%			15.3%	59.6%		

Remarks: